


Stainless Steel Ball Lock Cable Ties, Uncoated

Technical Information:

- Material** A) 316 grade non-magnetic stainless steel
B) 304 grade non-magnetic stainless steel
- Temperature Range** - 80°C to + 500°C
- Surface Finish** Metallic
- Flamability rating** Absolutely fireproof. Halogen free and UV-resistant



Ball Lock Uncoated-SS304, 4.6mm width

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BU44-100	SS304	0.18	4.6	4	100	0.01	0.25	1.1	27	667	150	100/bag
BU44-150	SS304	0.18	4.6	6	150	0.01	0.25	1.7	43	667	150	100/bag
BU44-200	SS304	0.18	4.6	8	200	0.01	0.25	2.3	59	667	150	100/bag
BU44-260	SS304	0.18	4.6	10	260	0.01	0.25	3.1	78	667	150	100/bag
BU44-360	SS304	0.18	4.6	14	360	0.01	0.25	4.3	110	667	150	100/bag
BU44-520	SS304	0.18	4.6	20	520	0.01	0.25	6.3	161	667	150	100/bag
BU44-620	SS304	0.18	4.6	24	620	0.01	0.25	7.6	192	667	150	100/bag
BU44-840	SS304	0.18	4.6	33	840	0.01	0.25	10.4	263	667	150	100/bag
BU44-1000	SS304	0.18	4.6	39	1000	0.01	0.25	12.3	313	667	150	100/bag

Ball Lock Uncoated-SS316, 4.6mm width

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BU46-100	SS316	0.18	4.6	4	100	0.01	0.25	1.1	27	667	150	100/bag
BU46-150	SS316	0.18	4.6	6	150	0.01	0.25	1.7	43	667	150	100/bag
BU46-200	SS316	0.18	4.6	8	200	0.01	0.25	2.3	59	667	150	100/bag
BU46-260	SS316	0.18	4.6	10	260	0.01	0.25	3.1	78	667	150	100/bag
BU46-360	SS316	0.18	4.6	14	360	0.01	0.25	4.3	110	667	150	100/bag
BU46-520	SS316	0.18	4.6	20	520	0.01	0.25	6.3	161	667	150	100/bag
BU46-620	SS316	0.18	4.6	24	620	0.01	0.25	7.6	192	667	150	100/bag
BU46-840	SS316	0.18	4.6	33	840	0.01	0.25	10.4	263	667	150	100/bag
BU46-1000	SS316	0.18	4.6	39	1000	0.01	0.25	12.3	313	667	150	100/bag

Ball Lock Uncoated-SS304, 7.9mm width

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BU74-100	SS304	0.31	7.9	4	100	0.01	0.25	1.1	27	1335	300	100/bag
BU74-150	SS304	0.31	7.9	6	150	0.01	0.25	1.7	43	1335	300	100/bag
BU74-200	SS304	0.31	7.9	8	200	0.01	0.25	2.3	59	1335	300	100/bag
BU74-260	SS304	0.31	7.9	10	260	0.01	0.25	3.1	78	1335	300	100/bag
BU74-360	SS304	0.31	7.9	14	360	0.01	0.25	4.3	110	1335	300	100/bag
BU74-520	SS304	0.31	7.9	20	520	0.01	0.25	6.3	161	1335	300	100/bag
BU74-620	SS304	0.31	7.9	24	620	0.01	0.25	7.6	192	1335	300	100/bag
BU74-840	SS304	0.31	7.9	33	840	0.01	0.25	10.4	263	1335	300	100/bag
BU74-1000	SS304	0.31	7.9	39	1000	0.01	0.25	12.3	313	1335	300	100/bag

Ball Lock Uncoated-SS316, 7.9mm width

Part No.	Material	Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
		In	mm	In	mm	In	mm	In	mm	N	lbs	
BU76-100	SS316	0.31	7.9	4	100	0.01	0.25	1.1	27	1335	300	100/bag
BU76-150	SS316	0.31	7.9	6	150	0.01	0.25	1.7	43	1335	300	100/bag
BU76-200	SS316	0.31	7.9	8	200	0.01	0.25	2.3	59	1335	300	100/bag
BU76-260	SS316	0.31	7.9	10	260	0.01	0.25	3.1	78	1335	300	100/bag
BU76-360	SS316	0.31	7.9	14	360	0.01	0.25	4.3	110	1335	300	100/bag
BU76-520	SS316	0.31	7.9	20	520	0.01	0.25	6.3	161	1335	300	100/bag
BU76-620	SS316	0.31	7.9	24	620	0.01	0.25	7.6	192	1335	300	100/bag
BU76-840	SS316	0.31	7.9	33	840	0.01	0.25	10.4	263	1335	300	100/bag
BU76-1000	SS316	0.31	7.9	39	1000	0.01	0.25	12.3	313	1335	300	100/bag